



FOREHEARTH LENGTH (FEET)	DIMENSION		416		426				436				443				448				
	A	B	FRONT	REAR	FRONT	INTER 1	INTER 2	REAR	FRONT	INTER 1	INTER 2	REAR	FRONT	INTER 1	INTER 2	REAR	FRONT	INTER 1	INTER 2	REAR	
8	-	-	2.7	0.1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
10	-	-	2.8	0.6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
12	-	-	2.9	1.0	3.3	-	-	1.4	-	-	-	-	-	-	-	-	-	-	-	-	-
14	-	-	3.1	1.3	3.5	-	-	1.8	4.0	-	-	2.2	-	-	-	-	-	-	-	-	-
16	-	-	3.3	1.7	3.8	-	-	2.2	4.3	-	-	2.6	5.0	-	-	3.1	-	-	-	-	-
18	2565	-			2.8	3.1	-	0.9	3.1	3.6	-	1.0	3.6	4.3	-	1.2	-	-	-	-	-
20	2565	-			2.7	3.4	-	1.3	3.1	4.0	-	1.5	3.5	4.8	-	1.8	3.8	5.4	-	2.0	-
22	3175	-			2.9	3.9	-	1.2	3.4	4.6	-	1.4	3.9	5.5	-	1.6	4.2	6.1	-	1.8	-
24	3175	-			2.9	4.3	-	1.5	3.3	5.0	-	1.8	3.8	6.0	-	2.1	4.1	6.7	-	2.4	-
26	3785	-			3.1	4.8	-	1.4	3.6	5.6	-	1.7	4.2	6.6	-	2.0	4.6	7.4	-	2.2	-
28	2565	2438			3.0	2.5	3.3	1.4	3.3	3.0	3.8	1.7	3.8	3.6	4.5	2.0	4.1	4.0	4.6	2.2	-
30	2565	3048							3.2	3.5	4.3	1.6	3.7	4.1	5.0	1.9	4.0	4.6	5.6	2.1	-
32	3175	3048							3.6	4.1	4.1	1.6	4.1	4.8	4.8	1.9	4.5	5.4	5.4	2.2	-
34	3175	3048											4.0	4.7	5.5	2.4	4.4	5.3	5.7	2.6	-
36	3175	3658											4.0	5.3	5.7	2.2	4.3	5.9	6.3	2.5	-

FOREHEARTH WIDTH	ROLLER CENTRES		
	COND SECTION DIM X	COOL SECTION DIM Y	REAR SUPPORT DIM Z
416	1010	1000	935
426	1263	1253	1188
436	1676	1666	1601
443	1895	1885	1820
448	2155	2145	2080

NOTE - DIMENSIONS ARE IN MILLIMETERS AND SUPPORT LOADS ARE IN TONNES FOR U.S. TONS MULTIPLY LOADS GIVEN BY 1.1023 THESE ARE THE ACTUAL SUPPORT LOADS. ALL SUPPORTING STEELWORK SHOULD BE DESIGNED TO TAKE AT LEAST THE MAXIMUM FOR THE FOREHEARTH WIDTH. (I.E FOR 426 FOREHEARTH STEELWORK SHOULD BE CAPABLE OF SUPPORTING A LOAD OF AT 4.8 TONNES).